



# Product Data Sheet

## Q80 Aerosol

Low VOC Contact Adhesive

### Q80 Low VOC Contact Adhesive

#### Features

- High Temperature, High Strength
- Quick Tack Formula
- Water-Resistant Bond
- Meets and Exceeds the SCAQMD Rule 1168
- Great for Multiple Substrates

#### Description

Quality Aerosols Q80 is a high strength, high shear and fast tack adhesive. Our adhesive is specially formulated for making permanent bonds. Q80 Adhesive is most effective when both surfaces are coated. It can be used on all types of wood, most metals, all laminates and veneers and many other substrates. Q80 is a high solids adhesive with a quick tack time, is resistant to high temperatures and has a water resistant bond.

#### Applications

Used for the permanent bonding of wood, metal, laminates, veneers, plastics, cloth, fiberglass insulation and other substrates.

#### Product Usage

80Q Adhesive is designed as a two surface bonding application. All surfaces should be tested for compatibility. Surfaces need to be dry and free of oil and debris. Spray an even coat of adhesive to cover 85%-100% of the surfaces. Allow adhesive to dry 3-5 minutes until it becomes tacky. For porous surfaces it is recommended to apply a second coat after the first coat has become tacky. Put the coated surfaces together and apply pressure. Full adhesive strength will be reached in 24 hours.

#### Storage

Store in a cool, dry, and well ventilated area. Do not handle or store near open flame or other heat sources. We recommend storing at or above 65°F. Bulk and canister products should be kept off the floor.

## Product Specifications

Color	Natural or Red
Solids	38.0% +/- 2%
VOC Content	37%
VOC Compliant CARB/OTC	Yes
Bonding Range	30 minutes
Dry/Tack Time	3-5 minutes
Spray Pattern	Web
Sizes Offered	14 oz
Warranty Period	1 Year from manufacture date
Square Feet Coverage	approx. 50 ft <sup>2</sup> @ 2.5g
Tip for Spraying	Spraying Systems 9501AB, 6501AB

**Note:** All results are based on 2.5g dried glue/ft<sup>2</sup>

